



# 61.2HP Tractor with 2WD/4WD Drive

Our 2WD/4WD Drive Tractors are built safe, steady and sturdy for on and of road tough Africa conditions, are uncomplicated to use and offer the best safety features as standard. Toma Equipment supports all its tractors with qualified support personnel and extensive parts availability.



FRONT  
WEIGHT  
CARRIER

CAT II  
3 POINT  
LINKAGE

**SAFE | STRONG | STURDY**

**DI 6565**


[www.toma.co.za](http://www.toma.co.za)



### Weight

Front Weight carrier  
(hanging weight and optional)

Rear Weight Optional



### Brakes


Oil Immersed Brake, Mechanically actuated with Pawl and Ratchet Type Hand Brake



### Dimension & Weight


2W/D 2266Kg in Weight, 2150mm Wheel Base, 3800mm in total length, 1980mm in total width, 2620mm in Height (ROPS), 450mm Ground Clearance. Between 1360mm - 1710mm Front Track and 1950mm Rear Track.

4W/D 2850Kg in Weight, 2234mm Wheel Base, 3840mm in total length, 1980mm in total width, 2620mm (ROPS) in Height, 390mm Ground Clearance. 1480mm Front Track and 1950mm Rear Track.



### Steering

Power Steering



### Electrical System

12,88V,Ah Battery  
12,42V,A Alternator  
Seven Pin (Round) Trailer Socket



### Capacity

65l Fuel Tank, 1.8l Power Steering System, 12l Engine Oil,  
2 W/D 44l Hydraulic & Transmission  
4 W/D 45l Hydraulic & Transmission




### Speed Forward

Max: 1.50Km/h@2200RPM  
Min: 30.84Km/h@2200RPM



### Engine

A65 (Cold Start Kit Optional) 61.2/45HP/kW, Four Cylinder, naturally aspirated, 105/118mm Bore/Stroke, 4088cc, 2200RPM, Dry Air Cleaner with Clogging Sensor, 255Nm@1450RPM




### PTO

Independent PTO@540/540 E  
Mechanically actuated and Hand Operated



### Transmission

2W/D or 4W/D with dual clutch and 12F+12R Gearbox. Synchromesh with F/R Synchro Shuttle



### Turning Diameter

2W/D  
With Brakes (m) 7.85 (L) -7.6 (R)  
Without Brakes (m) 9.40 (L) -9.35 (R)

4W/D  
With Brakes (m) 9.40 (L) -9.00 (R)  
Without Brakes (m) 10.40 (L) -10.75 (R)



### Hydraulic System

Automatic Draft Control, CAT II 3 Point Linkage, 1SA +1DA  
2200Kg Hydraulic Lifting Capacity at ball ends



### Other

Horizontally Adjustable Driver Seat with SMV Emblem  
Fuel Indicator Gauge and Front Tow Hook  
DCV



### Tyres

2W/D 4W/D  
Front 7.50X16 Front 11.2X24  
Rear 16.9X28 Rear 16.9X28

# SPECIFICATIONS DI 6500